



## **Technical Datasheet Arbo Bond Breaker Tape**

Arbo Bond Breaker Tape is a laminated polyethylene cloth tape combined with a pressure sensitive adhesive backing. The laminated polyethylene prevents sealant adhesion to ensure that the sealant does not form a three sided adhesive bond. High bond strength of the pressure sensitive adhesive ensures good adhesion to a variety of common construction substrates. Bond Breaker Tape has good conformability ensuring good adhesion to both regular and irregular surfaces.

### **Main Applications**

Recommended for sealant joints to ensure that the sealant adheres to the two principle surfaces of the joint only. Bond breaker tape prevents adhesion to the back of the joint. Three sided adhesion can lead to sealant splitting, cracking and early joint failure.

### **Packaging**

50m x 4.5mm  
50m x 20mm  
50m x 6mm  
50m x 10mm  
50m x 12mm

### **Colours**

Black

### **Application**

All surfaces to be bonded must be clean and dry.

### **Shelf Life**

Not applicable if product is stored in a cool, dry place out of direct sunlight.

### **Health and Safety.**

No hazards associated with the product.

### **Technical Data**

Thickness: 0.2 mm

Application Temperature: + 5° C to + 40° C



Service Temperature: - 50° C to + 150° C

Tensile Strength: 110 – 115 N/25mm

**Important:** The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

Adshead Ratcliffe, Derby Road, Belper, Derbyshire DE56 1WJ, England.

**Telephone: 01773 826661**

**Fax: 01773 821215**

**Internet: [www.arbo.co.uk](http://www.arbo.co.uk)**