

**DENSO SKID RESISTANT OVERBANDING TAPE**

DESCRIPTION A polymer modified bituminous tape for surface sealing of cracks or failed reinstatement joints up to 5mm wide in road pavements on secondary roads. Application of the tape prevents ingress of water which can cause further cracking and spalling of the road surface. Once applied the tape has a skid resistant surface. Suitable for hand or machine application.

COMPOSITION Thick bituminous adhesive layer with a rubber based backing in tape form with a disposable release paper.

TYPICAL PROPERTIES	DATA
Softening Point of Adhesive	120°C
Resistance to Water, Acids, Alkalis and Salts	Excellent
Skid Resistance (TRL Road Note 27)	Dry 67 Wet 66 Exceeds Dept for Transport Requirement
Thickness	2.8mm
Roll Length	10 metres
Tape Widths	30mm and 40mm
Core Size	76mm ID
Temperature Range for application	8°C-45°C

PACKING	10 rolls x 30mm or 8 rolls x 40mm per carton
---------	--

RECOMMENDED PRIMER	Densoband Primer
--------------------	------------------

APPLICATION MACHINE	Denso Roller 75 applicator
---------------------	----------------------------

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9002 1994 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net