





The Wykamol Mould Control System (MCS) is a two stage treatment for walls, ceilings etc. affected by condensation mould. When our recommendations are followed, and both stages are completed, surfaces will exhibit excellent resistance to mould growth even under severe condensation conditions. Typically, full control can be achieved for up to 5 years but this can be extended considerably where moisture control measures are implemented (we are able to advise on issues such as ventilation, insulation and heating control, all of which can reduce the causes of condensation).

DESCRIPTION

Supplied as a 5X concentrate, this product is designed to provide an initial wash/ sterilisation treatment to remove and kill mould spores and surface growths on painted or papered surfaces. We recommend the wash is applied before removing mould-damaged paint or paper (to minimize spread of viable spores). When applied liberally to papered surfaces it can be an effective stripping agent. After the first wash, and once damaged paper or plaster has been removed, it is necessary to apply a second wash with Mould Clear solution to leave the surface clean and remove any residues of dead spores etc. It is recommended that mould affected woodchip and Anaglypta papers are always removed and arenot recommended for re-instatement.

Based on established active ingredients, the Mould Clear solution both cleans and sterilises the surface as the first stage towards redecoration. Alternatively, it can be used singly, as required, to control spore



development where other measures are to be completed at a later time.

INSTRUCTIONS FOR USE

Dilute one part of concentrate with 4 parts of warm water. Apply diluted solution at a rate of 1 litre per 10 m2 with a brush, sponge or cloth, extending the wash area at least one metre beyond signs of surface mould growth. Repeat as necessary to remove surface spores and dirt. Allow to dry before continuing.

TECHNICAL INFORMATION

The information contained in this data sheet is for professional preservation specialists and is compiled accordingly.

Further information and advice is freely Available from the Wykamol Technical Department.

The company warrants this product to be of merchantable quality and fit for the purpose designed, providing that any instructions relating to use, handling and storage are duly observed. All transactions subject to our standard.

Conditions of sale, copies available on request.









